

13th European Conference on Industrial Furnaces and Boilers – INFUB-13



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Algarve, Portugal

19th – 22nd April 2022

Adaption of a 300 kW_{th} Pilot Plant for Testing the Indirectly Heated Carbonate Looping Process for CO₂ Capture from Lime and Cement Industry


Carina Hofmann*, Martin Greco-Coppi*, Jochen Ströhle*, Bernd Epple*

* Technical University Darmstadt, Energy Systems and Technology, Otto-Berndt-Str. 2, 64287 Darmstadt, Germany

1 Introduction, Process Integration



- Cement and lime industry accounts for over 8 % of global fossil CO₂ emissions [1]
- More than 50 % of CO₂ emissions are unavoidable
- 14 -33 % of CO₂ in exhaust gas [2]



- Using synergies
- Aiming net negative CO₂ emissions
- Reduce CO₂ avoidance costs

[1] European Commission (JRC), Trends in global CO₂ emissions, 2016


[2] Bosoaga et. al, 2009




1 Introduction, Process Scheme IHCaL



TECHNISCHE
UNIVERSITÄT
DARMSTADT



- **High efficiency** (1.5 – 2 % points efficiency drop)
- **Few impurities** (sulfur, ash)
- Technology validated in pilot scale





2

Experimental Reactors 300 kW_{th} Pilot Plant



TECHNISCHE
UNIVERSITÄT
DARMSTADT

	Carbonator	Calciner	Combustor
Thermal load/ duty	300 kW _{th} flue gas load	~ 180 kW _{th}	~ 310 kW _{th}
Solid inventory	30 – 60 kg (CaO/CaCO ₃)	400 kg (CaO/CaCO ₃)	600 kg (silica sand)
Superficial velocity (u_o)	2.5 – 7 m/s	0.2 – 0.4 m/s	0.4 – 1.6 m/s



2


Experimental IHCaL Configuration



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Solid flow

- Solid sampling




2

Experimental IHCaL Configuration




TECHNISCHE
UNIVERSITÄT
DARMSTADT

Gas flow




Overview



2 Experimental Adaption Flue Gas Path




TECHNISCHE
UNIVERSITÄT
DARMSTADT



Experimental Results

Reactor Temperature Profile




Carbonator

- Inventory: 900 - 3000 kg/m²
- $y_{\text{CO}_2,\text{in}}$: ~ 12 vol.-%
- Active reactor cooling

Calciner

- Inventory: 1050 - 1300 kg/m²
- Air fluidisation




3

Experimental Results Carbonator Efficiency



TECHNISCHE
UNIVERSITÄT
DARMSTADT



- Each set point (SP) state of at least 3 hours
- Temperature dependency with decreased inventory
- Capture efficiency with real gas up to 90 %

- With stable inventory & moisture content in gas
- $E_{Carb} > 90$ % possible





4

Further Steps



TECHNISCHE
UNIVERSITÄT
DARMSTADT

- Analysis and evaluation of sorbent samples
 - Process performance and usage as educts for concrete
- Improvement of global circulation
- Usage of different solid materials; SRF and cement raw meal



Generation of **experimental data** via **long-term pilot testing** under **real conditions**



Acknowledgement



TECHNISCHE
UNIVERSITÄT
DARMSTADT


This project ANICA is funded through the ACT programme (Accelerating CCS Technologies, Horizon2020 Project No 294766). Financial contributions made from the German Federal Ministry of Economic Affairs and Energy based on a resolution of the German Parliament under grant no. 03EE5025, are gratefully acknowledged.

Supported by:




Federal Ministry
for Economic Affairs
and Energy

on the basis of a decision
by the German Bundestag



Thank you for your Attention!



Dipl.-Ing. Carina Hofmann
Technical University Darmstadt
Institute for Energy Systems and
Technology
Carina.hofmann@est.tu-darmstadt.de



“Adaption of a 300 kW_{th} Pilot Plant for Testing the Indirectly Heated Carbonate Looping Process for CO₂ Capture from Lime and Cement Industry” © 2022 by Carina Hofmann, Martin Greco-Coppi, Jochen Ströhle, and Bernd Eppler is licensed under [CC BY 4.0](https://creativecommons.org/licenses/by/4.0/).